


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A47L 9/04, 5/30		(11) International Publication Number: WO 00/21426	
A1		(43) International Publication Date: 20 April 2000 (20.04.00)	
(21) International Application Number: PCT/GB99/03270 (22) International Filing Date: 4 October 1999 (04.10.99) (30) Priority Data: 9822001.5 8 October 1998 (08.10.98) GB (71) Applicant (for all designated States except US): NOTETRY LIMITED [GB/GB]; Kingsmead Mill, Little Somerford, Wiltshire SN15 5JN (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): STEVENS, Evan, James [GB/GB]; 5 Smith's Field, Cirencester, Gloucestershire GL7 1XX (GB). (74) Agents: SMITH, Gillian, Ruth et al.; Dyson Research Limited, Intellectual Property Dept., P.O. Box 2080, Malmesbury, Wiltshire SN16 0SW (GB).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report.	

(54) Title: A CLEANER HEAD ASSEMBLY FOR A VACUUM CLEANER



(57) Abstract

The invention provides a cleaner head assembly for a vacuum cleaner comprising a cleaner head body (10) rotatably mountable on the main body (102) of a vacuum cleaner (100), a brush housing (110) rotatably mounted on the cleaner head body (10) and having a dirty air inlet (112), a dirty air outlet and a brush bar (26) mounted in the dirty air inlet (112), wherein the brush housing (110) has a projecting arm (30) carrying a cam follower (32) for contacting a cam surface (34) located on the main body (102) of the vacuum cleaner (100), the cam surface (34) being adapted to maintain the dirty air inlet (112) in a horizontal plane. This maintains good suction through the cleaner head during cleaning.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

A Cleaner Head Assembly for a Vacuum Cleaner

The present invention relates to a cleaner head assembly for a vacuum cleaner.

An upright vacuum cleaner normally comprises a main body containing dirt and dust separating apparatus, a cleaner head rotatably mounted on the main body and having a dirty air inlet, and a motor and fan unit for drawing dirty air into the dirt and dust separating apparatus via the dirty air inlet so that dirt and dust can be separated from the airflow before the clean air is expelled to the atmosphere. The dirty-air inlet through which dirty air is sucked into the vacuum cleaner is directed downwardly so that it faces the floor to be cleaned. The dirt and dust separating apparatus can take the form of a filter bag or, as is known, can alternatively take the form of a cyclonic arrangement. The present invention is not concerned with the nature of the dirt and dust separating apparatus and is therefore applicable to vacuum cleaners utilising either arrangement.

A brush bar is supported in the dirty-air inlet so that it protrudes to a small extent from the inlet. The brush bar is activated mainly when the vacuum cleaner is used to clean carpeted surfaces. The brush bar comprises an elongate cylindrical core from which bristles extend along its length in a radial direction. The brush bar is driven by the motor via a drive belt so that the brush bar rotates within the inlet. Rotation of the brush bar causes the bristles to sweep along the surface of the carpet to be cleaned to loosen dirt and dust and pick up debris. The suction of air causes air to flow around the brush bar and underneath it to help lift the dirt and dust from the surface to be cleaned and then carry it from the dirty-air inlet to the dirt and dust separating apparatus.

It will be appreciated that the effectiveness of an upright vacuum cleaner will depend upon the amount of dirt and dust which can be picked up by the cleaner head and passed to the dirt and dust separation apparatus. For each vacuum cleaner there is an optimum configuration for the relationship between the dirty-air inlet and the carpet to be cleaned. Very often, the relationship will be one that maintains the dirty-air inlet in a plane which is parallel to the floor so that the mouth of the inlet is horizontal. Ideally then, the dirty

air inlet should be maintained completely horizontal to the floor so that the maximum amount of air is sucked into the dirty air inlet travels through the fibres of the carpet being cleaned before travelling on through the cleaner to the dirt and dust separating apparatus. However, the angle of the cleaner head to the horizontal may differ when the vacuum cleaner is used on different types of floor surface, eg on carpets with different piles and textures. Also, the vacuum cleaner is in use moved over the surface to be cleaned in reciprocating forwards and backwards movements so that the cleaner head travels both forwards and backwards over the surface whilst collecting dust and dirt via the dirty air inlet. In most cases the cleaner head will be acted upon in different ways by the carpet when it is travelling in different directions and will not maintain good contact on all sides of the dirty air inlet in both directions. Furthermore, the action of the user can result in the angle of inclination of the handle to the vertical being varied quite significantly during normal use and this can cause the plane of the dirty air inlet to be lifted, either at the front or the back, away from the horizontal. Any and all of these things can result in a reduction in the effectiveness of the suction of the cleaner head which can lead to a loss in the maximum level of pick-up and then to customer dissatisfaction.

Some attempts have been made to solve this problem by way of manually operated cleaner head lifting and lowering mechanisms by means of which the user is able to set the optimum height for the cleaner head when the cleaner is being used on a particular surface. However, these mechanisms only lift and lower the cleaner head by pivoting about the axis about which the cleaner head is connected to the main body of the cleaner. They do not address the problem of the dirty air inlet becoming inclined to the horizontal and thereby allowing the inlet suction to become less effective. One effective way to address this problem has been described in our copending UK patent application no. 9725777.8 which gives full details of a cradle-type arrangement for mounting the brush bar in the dirty air inlet. The brush bar is mounted in a cradle which is itself freely rotatably mounted in the cleaner head. The difficulty associated with this arrangement is that the cradle must be sealed with respect to the cleaner head and this can be difficult to achieve. The cradle must remain freely rotatable with respect to the cleaner head whilst preventing any loss of suction during use of the vacuum cleaner.

The constant movement of the cradle with respect to the cleaner head affects the life of the seal between the cradle and the cleaner head so that the seal can be prone to leakages in a relatively short time.

An object of the present invention is to provide a cleaner head which maintains the suction opening of the dirty air inlet in contact with the surface to be cleaned throughout cleaning. A further object of the invention is to provide a cleaner head assembly which remains horizontal during cleaning. A still further object of the invention is to provide a cleaner head for a vacuum cleaner which has improved pick-up capabilities. A further object is to provide a cleaner head assembly which requires less maintenance than known assemblies.

The present invention provides a cleaner head assembly as claimed in Claim 1. The invention also provides a vacuum cleaner as claimed in Claim 13. Preferred features are set out in the subsidiary claims.

The provision of a cam follower on the brush housing maintains the dirty air inlet in a substantially horizontal plane, irrespective of the type of carpet being cleaned, the direction of movement of the cleaner head and the angle of inclination of the handle to the vertical. The maintenance of the dirty air inlet in a horizontal plane ensures a good, even distribution of airflow through the inlet and around the brush bar. This in turn improves the pick-up performance of the cleaner head assembly.

The preferred arrangement of the brush housing being pivotable with respect to the cleaner head body about an axis coincident with that of the brush bar is a convenient and easily manufactured construction. Providing a biasing member between the cleaner head body and a rear portion of the brush housing ensures that the cam follower is maintained in contact with the cam surface at all times. This ensures reliable operation of the mechanism.

An embodiment of the invention will now be described with reference to the accompanying drawings, wherein:

Figure 1 is a side view of a vacuum cleaner incorporating a cleaner head assembly according to the present invention;

Figure 2 is a side view of the vacuum cleaner of Figure 1 with the handle shown in an inclined position;

Figure 3 is a sectional view of the cleaner head of the cleaner of Figures 1 and 2 in a first position;

Figure 4 is a sectional view of the cleaner head of the cleaner of Figures 1 and 2 in a second position; and

Figure 5 is a sectional view of the cleaner head of the cleaner of Figures 1 and 2 in a third position.

Figures 1 and 2 illustrate the overall construction of an upright vacuum cleaner incorporating a cleaner head assembly according to the invention. The vacuum cleaner 100 has a main body 102 in which dust separation apparatus 104 is housed. In this embodiment the dust separation apparatus 104 comprises cyclonic dust separation apparatus consisting of two cyclones arranged in series. Apparatus of this type is well known and will not be described any further here because it has no material effect on the invention. A motor housing 106 is located at the lower end of the main body 102 and forms part of the main body 102. Supporting wheels 107 are mounted directly on the side of the motor housing 106. A cleaner head assembly 108 is rotatably mounted on the motor housing 106 about an axis A. The cleaner head assembly 108 has a brush housing 110 with a downward facing inlet 112 arranged at the forward end of the cleaner head assembly 108. A flexible duct 114 extends between the brush housing 110 and a dirty air inlet in the main body 102 which communicates with ducting which leads to the dust separation apparatus 104.

A handle 116 extends upwardly from the lower part of the main body 102 and lies alongside the rear part of the main body 102. When the cleaner 100 is to be used in the upright mode (as shown in Figure 1), the handle 116 extends upwardly beyond the main body 102 so that it can be gripped by a user and used to manoeuvre the cleaner 100 across a surface to be cleaned. The handle 116 is, however, releasable and may alternatively be used as a hose and wand assembly. This can be achieved in several

ways and examples are shown and described in EP 0 037 674 and EP 0 134 654. The lower end of the hose/wand 116 is also connected via ducting 118 to the dirty air inlet of the main body 102 to allow dirt and dust entering the cleaner 100 via the hose and wand to be passed to the dust separation apparatus 104.

A changeover valve (not shown) is provided in order that the appropriate inlet can be automatically selected for different modes of operation. When the cleaner 100 is in the position shown in Figure 1, the changeover valve automatically connects the dust separating apparatus 104 to the wand and hose 116 so that cleaner can be used in cylinder mode for above the floor cleaning. Air is drawn into the cleaner through the distal end 116a of the wand which can be released from the cleaner for appropriate manipulation. The inlet 112 in the cleaner head assembly 108 is automatically shut off. When the cleaner 100 is to be used in conventional upright mode, the handle is restored to the position shown in Figure 1 and then inclined to the vertical as shown in Figure 2. The changeover valve automatically shuts off the air inlet at the distal end 116a of the wand and connects the dust separating apparatus 104 to the inlet 112 in the cleaner head assembly 108. The construction of the changeover valve does not form part of the present invention and will not be described any further here.

In all cases, ie in the upright mode and in the cylinder mode, a motor (not shown) located in the motor casing 106 drives a fan (also not shown) so as to draw air into the cleaner 100 via the appropriate inlet, conduct it to the dust separating apparatus 104 in the main housing 102 and then expel the cleaned air to the atmosphere. The cleaned air is preferably caused to flow past the motor so as to cool it before being expelled.

Figures 3 to 5 show in more detail the cleaner head assembly 108 forming part of the vacuum cleaner 100 shown in Figures 1 and 2. The cleaner head assembly 108 has a cleaner head body 10 comprising a front portion 12 extending laterally across the width of the vacuum cleaner 100 and two rearwardly extending side arms 14 extending rearwardly from the side portions of the front portion 12. Each side arm 12 has a lug 16 which defines an aperture centred on the axis A about which the cleaner head assembly 108 is pivotably mounted on the motor casing 106. The cleaner head assembly 108 is

mounted on the motor casing by way of pins 18 which extend through the apertures in the lugs. The cleaner head assembly 108 pivots freely about the axis A so as to "float" on the floor to be cleaned without requiring the user to identify and set a predetermined level at which the cleaner head must operate.

The cleaner head assembly 108 includes a brush housing 110. The brush housing 110 is pivotably mounted on the front portion 12 of the cleaner head body 10 by way of lugs (not shown) depending from the side portions of the front portion 12. The brush housing 110 is manufactured from an upper plate 20 and a lower plate 22 which may be made from plastics material or a metal such as stainless steel. The upper and lower plates 20, 22 are joined together by quarter turn fasteners (not shown), by press-fitting or by other suitable means. A seal 24 is trapped between the upper and lower plates 20, 22 so as to ensure that the seal between the plates 20, 22 is essentially airtight. Rollers 25 are rotatably mounted at the front edge of the lower plate 22 to support the brush housing 110 on the carpet or other surface to be cleaned. The rollers 25 can be positioned at or adjacent the outer edges of the lower surface 22 or, alternatively, can extend either continuously or in a spaced manner across the entire width of the brush housing 110.

A suction opening 112 is formed in the lower plate 22. The suction opening 112 extends across the entire width of the brush housing 110. A brush bar 26 is rotatably mounted in the brush housing 110 so that the bristles of the brush bar 26 protrude slightly out of the suction opening 112. The axis B about which the brush bar 26 rotates is coincident with the axis about which the brush housing 110 is pivotably mounted on the front portion 12 of the cleaner head body 10. The brush bar 26 is arranged to be drivable by the motor of the vacuum cleaner 100 in a conventional manner, for example, by way of a drive belt. The upper plate 20 of the brush housing 110 has a connection point (not shown) for connecting the brush housing 110 to an air inlet (not shown) on the main body of the vacuum cleaner 100. A flexible tube (not shown) connects the connection point with the air inlet. The flexible tube is made of any suitable material, for example, rubber or plastics.

Extending rearwardly from the brush housing 110 is a projecting arm 30. The projecting arm 30 is fixedly connected to or formed integrally with the brush housing 110 and is located beneath one of the side arms 14 adjacent the motor housing 102 of the vacuum cleaner. A wheel or roller 32 is pivotably mounted for free rotation on the distal end of the rearwardly projecting arm 30. A cam surface 34 is formed into the surface of the motor casing 106 facing the brush housing 110. The projecting arm 30 is located so that the wheel or roller 32 touches the cam surface 34 of the motor housing 106. The wheel or roller 32 then acts as a cam follower.

A hooked projection 36 is formed in the interior of the front portion 12 of the cleaner head body 10. A similar hooked projection 38 is formed on the rear portion of the brush housing 110. A resilient member 40 in the form of a tension spring is connected to both of the hooked projection 36, 38 and acts between the brush housing 110 and the cleaner head body 10 so as to bias them towards one another. This action ensures that the wheel or roller 32 remains in contact with the cam surface 34 at all times.

The shape of the cam surface 34 is specifically and deliberately designed to ensure that the brush housing 110 remains horizontal, or at least the suction opening 112 arranged in the lower plate 22 remains in a horizontal plane, at all angles of inclination of the handle 116 to the vertical. It will be appreciated that, because of the fact that the supporting wheels 107 are mounted directly on the side of the motor housing 106, the height of the axis A above the surface being cleaned changes with the angle of inclination of the handle 116. When the handle 116 is in a vertical position, as shown in Figure 3, the distance between the axis A and the profile of the cam surface 34 is sufficient to keep the projecting arm 30, and thereby the suction opening 112, substantially horizontal. As the handle 116 of the vacuum cleaner 100 is inclined with respect to the vertical during cleaning the wheels 107 are moved to a lower position with respect to the axis A so that the axis A is effectively lifted further away from the surface being cleaned. However, as is shown in Figure 4, the profile of the cam surface 34 is such that the distance between the axis A and the cam surface 34 is increased so as to maintain the wheel or roller 32 at the same level above the surface being cleaned as it was when the handle 116 was in a vertical position. The suction opening 112 is

therefore maintained in a horizontal plane and maximum performance is thus maintained. The same is true when the handle 116 is inclined even further away from the vertical as is shown in Figure 5. As the angle of inclination of the handle 116 increases, so the distance between the axis A and the cam surface 34 increases.

At all times, the tension spring 40 acts between the brush housing 110 and the cleaner head body 10 so as to bias the rear portion of the brush housing upwardly. The wheel or roller 32 is thereby maintained in constant contact with the cam surface 34 and is pressed thereagainst under the action of the spring 40. The spring 40 is under minimum tension when the handle 116 is in the vertical position.

Maintaining the suction opening in a horizontal plane maximises the efficacy of the cleaner head assembly during on the floor cleaning. The brush housing is no longer influenced by external factors such as differing carpet piles, direction of cleaner movement and differing angles of inclination of the handle to the vertical so that the brush housing can be tilted and the suction opening lifted away from the floor, at least on one side. Maintaining the suction opening in a horizontal plane maintains good suction through the fibres of the carpet being cleaned and thus maintains good pick-up by the cleaner head.

The invention is not limited to the precise details of the embodiment described above. It will be appreciated that the spring 40 can be replaced by any suitable resilient member such as a rubber or rubberised plastics band. Other variations and modifications will be apparent to a skilled reader.


CLAIMS:

1. A cleaner head assembly for a vacuum cleaner comprising a cleaner head body rotatably mountable on the main body of a vacuum cleaner, a brush housing rotatably mounted on the cleaner head body and having a dirty air inlet, a dirty air outlet and a brush bar mounted in the dirty air inlet, wherein the brush housing has a projecting arm carrying a cam follower for contacting a cam surface located on the main body of the vacuum cleaner, the cam surface being adapted to maintain the dirty air inlet in a horizontal plane.
2. A cleaner head assembly as claimed in Claim 1, wherein the projecting arm carries a roller or wheel for rolling contact with the cam surface.
3. A cleaner head assembly as claimed in Claim 1 or 2, wherein the projecting arm extends rearwardly from the cleaner head body.
4. A cleaner head assembly as claimed in any one of the preceding claims, wherein the brush housing is pivotably mounted on the cleaner head about an axis coincident with that of the brush bar.
5. A cleaner head assembly as claimed in any one of the preceding claims, wherein the brush housing is pivotably mounted on the cleaner head body about an axis which is located forwardly of the centre of gravity of the brush housing.
6. A cleaner head assembly as claimed in Claim 5, wherein a biasing member extends between the cleaner head body and a rear portion of the brush housing and exerts an upward force on the rear portion of the brush housing.
7. A cleaner head assembly as claimed in Claim 6, wherein, in use, the biasing member maintains the cam follower in contact with the cam surface.


8. A cleaner head assembly as claimed in Claim 6 or 7, wherein the biasing member comprises a tension spring.
9. A cleaner head assembly as claimed in any one of the preceding claims, wherein the brush housing is sealed save for the dirty air inlet and the dirty air outlet.
10. A cleaner head assembly as claimed in Claim 9, wherein the dirty air outlet comprises a flexible tube connectable to a dirty air inlet in the vacuum cleaner main body.
11. A cleaner head assembly as claimed in Claim 10, wherein the flexible tube is separate from the cleaner head body.
12. A cleaner head assembly substantially as herein described with reference to the accompanying drawings.
13. A vacuum cleaner having a cleaner head assembly as claimed in any one of the preceding claims and a main body, wherein the main body of the vacuum cleaner has a lower portion which carries a cam surface.
14. A vacuum cleaner as claimed in Claim 13, wherein the cam follower is maintained in contact with the cam surface.
15. A vacuum cleaner as claimed in Claim 13 or 14, wherein the cam surface has a profile such that, in use, the dirty air inlet remains horizontal as the cam follower moves along the cam surface.
16. A vacuum cleaner as claimed in any one of Claims 13 to 15, wherein the main body comprises a dirty air inlet and the dirty air outlet of the brush housing is connected to the dirty air inlet of the main body.

17. A vacuum cleaner as claimed in any one of claims 13 to 16, wherein the main body contains cyclonic dirt and dust separating apparatus.

18. A vacuum cleaner substantially as herein described with reference to the accompanying drawings.




2/5


**FIG. 2.**

SUBSTITUTE SHEET (RULE 26)


3/5



4/5



5/5



INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 99/03270

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A47L9/04 A47L5/30

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A47L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3 639 941 A (KIRWAN W J ET AL) 8 February 1972 (1972-02-08) abstract column 2, line 73 -column 3, line 69 figures	1
A	EP 0 727 171 A (STEIN & CO GMBH) 21 August 1996 (1996-08-21) abstract column 1, line 29 -column 2, line 17 column 2, line 28 -column 3, line 5 figures	1
A	DE 29 46 732 A (VORWERK & CO INTERHOLDING GMBH) 27 May 1981 (1981-05-27) page 3, paragraph 3 -page 5, paragraph 1 figures 1,2	1
	--- -/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

21 January 2000

Date of mailing of the international search report

31/01/2000

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Cabral Matos, A

INTERNATIONAL SEARCH REPORT

Inter. Appl. No.

PCT/GB 99/03270

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 32 39 347 A (VORWERK & CO INTERHOLDING GMBH) 26 April 1984 (1984-04-26) abstract page 6, line 22 -page 9, line 10 figures ---	1
P,A	WO 99 27834 A (NOTETRY LTD ET AL) 10 June 1999 (1999-06-10) cited in the application page 6, paragraph 4 -page 7, paragraph 3 figures 4,5 ---	1
A	EP 0 037 674 A (DYSON J) 14 October 1981 (1981-10-14) cited in the application page 8, line 6 - line 12 figure 8 ---	1
A	EP 0 134 654 A (ROTORK APPLIANCES LTD) 20 March 1985 (1985-03-20) cited in the application page 9, line 20 -page 10, line 2 page 19, line 9 -page 21, line 3 page 22, line 12 -page 23, line 20 figures 1-3,6,7 ---	1
A	US 5 331 715 A (CONNER W A ET AL) 26 July 1994 (1994-07-26) abstract column 7, line 63 -column 9, line 4 figures 1,2,5-10 -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/03270

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 3639941 A	08-02-1972	CA 937364 A GB 1290630 A	27-11-1973 27-09-1972
EP 0727171 A	21-08-1996	DE 19505106 A CA 2169591 A US 5819370 A	22-08-1996 17-08-1996 13-10-1998
DE 2946732 A	27-05-1981	AT 389438 B AT 566280 A CH 648473 A FR 2469902 A GB 2067066 A, B IT 1146063 B JP 56083321 A NL 8006101 A SE 8007941 A US 4360939 A	11-12-1989 15-05-1989 29-03-1985 29-05-1981 22-07-1981 12-11-1986 07-07-1981 16-06-1981 21-05-1981 30-11-1982
DE 3239347 A	26-04-1984	AT 22220 T AU 1993883 A EP 0109511 A ES 526573 A JP 59095027 A US 4531249 A	15-10-1986 03-05-1984 30-05-1984 01-07-1984 31-05-1984 30-07-1985
WO 9927834 A	10-06-1999	AU 1345299 A	16-06-1999
EP 0037674 A	14-10-1981	AT 14665 T CA 1162362 A DK 137581 A ES 501170 A HK 82386 A JP 1446407 C JP 56152617 A JP 62055416 B MY 10987 A NO 811013 A, B, US 4377882 A US RE32257 E	15-08-1985 21-02-1984 27-09-1981 01-07-1982 07-11-1986 30-06-1988 26-11-1981 19-11-1987 31-12-1987 28-09-1981 29-03-1983 07-10-1986
EP 0134654 A	20-03-1985	AT 41097 T AU 3108384 A CA 1241809 A DK 334384 A ES 534040 A WO 8500277 A GR 82013 A IE 55324 B JP 60501791 T NO 842728 A PT 78857 A, B US 4573236 A	15-03-1989 07-02-1985 13-09-1988 09-01-1985 01-05-1985 31-01-1985 12-12-1984 01-08-1990 24-10-1985 09-01-1985 01-08-1984 04-03-1986
US 5331715 A	26-07-1994	US 5467502 A	21-11-1995